




# SPECIFICATION SHEET

## Compact Commercial Water Softener Systems

### CC Series





Specifications		CC 206s	CC 206c	CC 208s	CC 208c
	Tank Size	6" x 13"	6" x 13"	8" x 17"	8" x 17"
	Resin Volume	0.18 ft <sup>3</sup>	0.18 ft <sup>3</sup>	0.4 ft <sup>3</sup>	0.4 ft <sup>3</sup>
	Service Flow	Upflow	Upflow	Upflow	Downflow
	Brine Tank Capacity	Optional	40 lb.	Optional	100 lb.
	Regeneration Volume	5 gallons	5 gallons	14 gallons	9 gallons
	Regeneration Time	11 minutes	11 minutes	11 minutes	11 minutes
	Peak Temperature	120°F	160°F	120°F	160°F
	Continuous Temperature	100°F	150°F	100°F	150°F
	Dimensions (WxDxH)	13 x 6 x 20 in.	14 x 14 x 22 in.	17 x 8 x 25 in.	20 x 24 x 28 in.
<b>Flow Meter Options</b>					
<b>Half Louver Nozzle (standard)</b>					
	Flow Range	0.3 - 9.1 gpm	0.3 - 9.1 gpm	0.3 - 10.2 gpm	0.3 - 10.2 gpm
	Meter Volume	583 gallons	583 gallons	732 gallons	732 gallons
	Salt Used	0.5 / 1.0 lbs.	0.5 / 1.0 lbs.	1.0 / 1.4 lbs.	1.0 / 1.4 lbs.
	Hardness Range	20 / 30 gpg	20 / 30 gpg	35 / 42 gpg	35 / 40 gpg
<b>Micro Nozzle (optional)</b>					
	Flow Range	0.05 - 0.15 gpm	0.05 - 0.15 gpm	0.05 - 0.15 gpm	0.05 - 0.15 gpm
	Meter Volume	61 gallons	61 gallons	61 gallons	61 gallons
	Salt Used	0.5 lbs.	0.5 lbs.	1.0 lbs.	1.0 lbs.
	Hardness Range	40	40	50	50
	Flow Range	0.15 - 5.0 gpm	0.15 - 5.0 gpm	0.15 - 5.0 gpm	0.15 - 5.0 gpm
	Meter Volume	250 gallons	250 gallons	315 gallons	315 gallons
	Salt Used	0.5 lbs.	0.5 lbs.	1.0 lbs.	1.0 lbs.
<b>Remote Start (optional)</b>					
	Minimum Flow*	0.05 gpm		0.05 gpm	
	Alternating Flow (15/30 psid)	9.5 - 15.5 gpm		10 - 16	
	Remote Start Control Time	4 minutes		4 minutes	
	Remote Start Pressure	20 - 100 psi		20 - 100 psi	
	Remote Start Flow	0.5 gpm		0.5 gpm	
	* Based on specification of external meter				